

Application story



Dosing

Location	Austria	Hydra-Cell model	P200MSGSSA07S
Type of application	Details not provided by customer	Flow rate	146.6 l/h (approximately)
Liquid	Water	Pressure	70 bar (Maximum)
Application details	Details not provided by customer		
Advantages of Hydra-Cell pump on this application	Hydra-Cell Metering Solutions incorporate multiple diaphragms which are not conventional and enable you to exceed API 675 performance standards, and meet ATEX compliance, with virtually pulse-less, linear flow. • No need for pulsation dampeners - saving installation and maintenance costs • Higher efficiencies • No pipe strain - no leakage • More compact design – Smaller footprint, lower acquisition and maintenance costs • Superior valves for abrasives, viscous and solids containing fluids • More control over the accuracy and consistency of flow rate - meets or exceeds API 675 • Non-lost motion design		

www.hydra-cell.co.uk

Wanner Engineering -
World Headquarters & Manufacturing
Minneapolis USA
t: (612) 332-5681
e: sales@wannereng.com

Wanner International
Hampshire UK
t: +44 (0) 1252 816847
e: sales@wannerint.com

Wanner Pumps
Shanghai CHINA
t: +86-21-6876 3700
e: sales@wannerpumps.com

Wanner Pumps
Kowloon HONG KONG
t: +852 3428 6534
e: sales@wannerpumps.com