


Application story


WANNERTM
HYDRA-CELL[®] PRO
SEAL-LESS PUMP TECHNOLOGIES



Fire Extinguisher Cylinder Filling

Location	India (Installation: 2010)	Hydra-Cell model	D10XKCTHHHA
Type of application	Cylinder Filling	Flow rate	9 l/min (2.4 GPM)
Liquid	3M TM Novec TM 1230 Fire Protection Fluid	Pressure	7-20 Bar (102-290 psi)
Application details	The aim of the skid is to compress gaseous liquid from a pressurised cylinder (depending on requirement) into smaller capacity cylinders - fire extinguishers The pump runs at speeds of 500 RPM, depending on volume injected in each can, and the discharge pressure is controlled with a regulation valve (adjusted by operator). The customer has been using the pump since 2010 without any maintenance any very happy with pump performance.		
Advantages of Hydra-Cell pump on this application	• Seal-less and packing-free design provides low maintenance • Capable of handling suction pressure up to 10 Bar and differential pressure up to 5 -10 Bar		

www.hydra-cell.co.uk

Wanner Engineering -
World Headquarters & Manufacturing
Minneapolis USA
t: (612) 332-5681
e: sales@wannereng.com

Wanner International
Hampshire UK
t: +44 (0) 1252 816847
e: sales@wannerint.com

Wanner Pumps
Shanghai CHINA
t: +86-21-6876 3700
e: sales@wannerpumps.com

Wanner Pumps
Kowloon HONG KONG
t: +852 3428 6534
e: sales@wannerpumps.com