

Application story


WANNERTM
HYDRA-CELL[®] PRO
SEAL-LESS PUMP TECHNOLOGIES



Polymer Injection for Enhanced Oil Recovery (EOR) (3)

Location	Argentina (Installation: January 2015)		Hydra-Cell model	D15XSGHFHCB
Type of application	Injecting Polymer		Flow rate	20K l/day (20 m ³ /day)
Liquid	Polymer		Pressure	69 bar (70 kg/cm ²)
Application details	A pilot plant is using 5 x Hydra-Cell D15 for their polymer injection process.			
Advantages of Hydra-Cell pump on this application	• Seal-less design enable reliable pumping of shear-sensitive liquids • The multiple diaphragm pump head of the Hydra-Cell pump produces virtually pulse-less flow on the suction making calibration more accurate			

www.hydra-cell.co.uk

Wanner Engineering -
World Headquarters & Manufacturing
Minneapolis USA
t: (612) 332-5681
e: sales@wannereng.com

Wanner International
Hampshire UK
t: +44 (0) 1252 816847
e: sales@wannerint.com

Wanner Pumps
Shanghai CHINA
t: +86-21-6876 3700
e: sales@wannerpumps.com

Wanner Pumps
Kowloon HONG KONG
t: +852 3428 6534
e: sales@wannerpumps.com