

 WANNER ENGINEERING, INC.	SPECIFICATION		PAGE 1 OF 1
	DESCRIPTION: MT8 Exceptions to API-675 3RD Edition, Errata 2, April 2015	DOCUMENT NO. 901-004	REVISION: A1
AUTHOR: D. Capriotti			DATE: 1/25/18

Summary

The following is a list of API 675 design requirements that are not currently fulfilled by the Hydra-Cell MT8 pump. This list is not exhaustive in detail, and it remains the responsibility of the Purchaser to specify all critical requirements prior to contract acceptance.

Exceptions to API 675 for MT8 Metering Pump

- 6.14.2.21 & 6.14.3.10** Hydra-Cell MT8 uses 316 SS bolts on cast iron drive case and drive case does not conform to ASTM 395
- 6.15.2** Hydra-Cell pumps do not feature rotational arrows. The standard Hydra-Cell nameplate is attached with aluminum rivets
- 6.15.3** Hydra-Cell nameplates consist of manufacturer information, serial number and model number
- 8.3.2.1 & 8.3.2.2** Hydrostatic testing is performed on request on pump head only
- 8.3.2.1.1** All hydrostatic and performance testing is conducted with city water
- 8.3.4.1** All tests are conducted in accordance with Hydra-Cell test procedures
- 8.4.1 - 8.4.3.9** No special coatings or preparation are made for shipping or storage unless requested.
- 8.4.3.5 & 8.4.3.6** Plastic shipping plugs are used